

## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 80 CRI | LO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	87	90	92	93
Total Lumens, 4' rail length (1219mm)	2589	2671	2725	2780
Lumens per foot (305mm)	647	668	681	695
Lumens per foot UP (305mm)	322	332	339	346
Lumens per foot DOWN (305mm)	325	335	342	349
Input Power (W), 4' rail length (1219mm)	29.9	29.9	29.9	29.9
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 80 CRI | SO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	108	111	113	116
Total Lumens, 4' rail length (1219mm)	5178	5342	5451	5560
Lumens per foot (305mm)	1294	1335	1363	1390
Lumens per foot UP (305mm)	645	665	678	692
Lumens per foot DOWN (305mm)	650	672	684	698
Input Power (W), 4' rail length (1219mm)	48.3	48.3	48.3	48.3
Watts per foot (305mm)	12.1	12.1	12.1	12.1
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 80 CRI | HO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	100	104	106	108
Total Lumens, 4' rail length (1219mm)	9838	10149	10356	10563
Lumens per foot (305mm)	2460	2537	2589	2641
Lumens per foot UP (305mm)	1224	1263	1289	1315
Lumens per foot DOWN (305mm)	1235	1274	1300	1326
Input Power (W), 4' rail length (1219mm)	98.4	98.4	98.4	98.4
Watts per foot (305mm)	24.7	24.7	24.7	24.7
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 90 CRI | LO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	75	78	79	81
Total Lumens, 4' rail length (1219mm)	2232	2302	2349	2396
Lumens per foot (305mm)	558	576	587	599
Lumens per foot UP (305mm)	278	287	292	298
Lumens per foot DOWN (305mm)	280	289	295	301
Input Power (W), 4' rail length (1219mm)	29.9	29.9	29.9	29.9
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 90 CRI | SO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	93	96	98	100
Total Lumens, 4' rail length (1219mm)	4464	4605	4699	4793
Lumens per foot (305mm)	1116	1151	1175	1198
Lumens per foot UP (305mm)	556	573	585	597
Lumens per foot DOWN (305mm)	561	578	590	602
Input Power (W), 4' rail length (1219mm)	48.2	48.2	48.2	48.2
Watts per foot (305mm)	12.1	12.1	12.1	12.1
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report

DoubleRace™ | 107 | 120° Batwing, Flat, up | 120° FlyWing™, Flat, down | 90 CRI | HO

107-DR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-G1G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	87	89	91	93
Total Lumens, 4' rail length (1219mm)	8481	8749	8928	9106
Lumens per foot (305mm)	2120	2187	1111	2277
Lumens per foot UP (305mm)	1056	1089	1121	1133
Lumens per foot DOWN (305mm)	1064	1099	2232	1143
Input Power (W), 4' rail length (1219mm)	98.4	98.4	98.4	98.4
Watts per foot (305mm)	24.7	24.7	24.7	24.7
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).