

## IES Report



# RaceRail® | 107 | 120° FlyWing™ | 80 CRI | LO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	86	89	91	93
Total Lumens, 4' rail length (1219mm)	1282	1322	1349	1376
Lumens per foot (305mm)	320	331	337	344
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# RaceRail® | 107 | 120° FlyWing™ | 80 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	107	110	113	115
Total Lumens, 4' rail length (1219mm)	2563	2644	2698	2752
Lumens per foot (305mm)	641	661	675	688
Input Power (W), 4' rail length (1219mm)	24.1	24.1	24.1	24.1
Watts per foot (305mm)	6.1	6.1	6.1	6.1
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# RaceRail® | 107 | 120° FlyWing™ | 80 CRI | HO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	99	103	105	107
Total Lumens, 4' rail length (1219mm)	4871	5024	5127	5230
Lumens per foot (305mm)	1218	1256	1282	1307
Input Power (W), 4' rail length (1219mm)	49.2	49.2	49.2	49.2
Watts per foot (305mm)	12.4	12.4	12.4	12.4
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



**IES Report**



**RaceRail® | 107 | 120° FlyWing™ | 90 CRI | LO**

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	74	77	78	80
Total Lumens, 4' rail length (1219mm)	1105	1140	1163	1186
Lumens per foot (305mm)	276	285	291	297
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# RaceRail® | 107 | 120° FlyWing™ | 90 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	92	95	97	99
Total Lumens, 4' rail length (1219mm)	2210	2280	2326	2373
Lumens per foot (305mm)	552	570	582	593
Input Power (W), 4' rail length (1219mm)	24.1	24.1	24.1	24.1
Watts per foot (305mm)	6.1	6.1	6.1	6.1
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



**IES Report**

**RaceRail® | 107 | 120° FlyWing™ | 90 CRI | HO**

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-G2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	86	89	90	92
Total Lumens, 4' rail length (1219mm)	4199	4331	4420	4508
Lumens per foot (305mm)	1050	1083	1105	1127
Input Power (W), 4' rail length (1219mm)	49.2	49.2	49.2	49.2
Watts per foot (305mm)	12.4	12.4	12.4	12.4
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).