

IES Report



RaceRail® | 107 | 120° Batwing Lens | 80 CRI | LO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-G1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	88	91	93	95
Total Lumens, 4' rail length (1219mm)	1313	1355	1383	1410
Lumens per foot (305mm)	328	339	346	353
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | 120° Batwing Lens | 80 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-G1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	110	113	115	118
Total Lumens, 4' rail length (1219mm)	2627	2710	2765	2820
Lumens per foot (305mm)	657	677	691	705
Input Power (W), 4' rail length (1219mm)	24.1	24.1	24.1	24.1
Watts per foot (305mm)	6.1	6.1	6.1	6.1
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | 120° Batwing Lens | 80 CRI | HO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-G1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	102	105	107	109
Total Lumens, 4' rail length (1219mm)	4991	5149	5254	5359
Lumens per foot (305mm)	1248	1287	1313	1340
Input Power (W), 4' rail length (1219mm)	49.2	49.2	49.2	49.2
Watts per foot (305mm)	12.4	12.4	12.4	12.4
CRI	85	85	85	85

Due to the large number of options in Vode’s product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | 120° Batwing Lens | 90 CRI | LO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-G1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	76	79	80	82
Total Lumens, 4' rail length (1219mm)	1132	1168	1192	1216
Lumens per foot (305mm)	283	292	298	304
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	96	96	96	96

Due to the large number of options in Vode’s product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | 120° Batwing Lens | 90 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-G1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	95	98	100	102
Total Lumens, 4' rail length (1219mm)	2264	2336	2384	2431
Lumens per foot (305mm)	566	584	596	608
Input Power (W), 4' rail length (1219mm)	24.1	24.1	24.1	24.1
Watts per foot (305mm)	6.1	6.1	6.1	6.1
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

RaceRail® | 107 | 120° Batwing Lens | 90 CRI | HO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-G1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	88	91	93	94
Total Lumens, 4' rail length (1219mm)	4303	4438	4529	4620
Lumens per foot (305mm)	1076	1110	1132	1155
Input Power (W), 4' rail length (1219mm)	49.2	49.2	49.2	49.2
Watts per foot (305mm)	12.4	12.4	12.4	12.4
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).