

IES Report



RaceRail® | 107 | Diffuse, round | 80 CRI | LO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	99	102	105	107
Total Lumens, 4' rail length (1219mm)	1477	1524	1555	1586
Lumens per foot (305mm)	369	381	389	396
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | Diffuse, round | 80 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	123	127	129	132
Total Lumens, 4' rail length (1219mm)	2954	3047	3110	3172
Lumens per foot (305mm)	739	762	777	793
Input Power (W), 4' rail length (1219mm)	24.1	24.1	24.1	24.1
Watts per foot (305mm)	6.1	6.1	6.1	6.1
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | Diffuse, round | 80 CRI | HO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	115	118	121	123
Total Lumens, 4' rail length (1219mm)	5613	5790	5908	6026
Lumens per foot (305mm)	1403	1448	1477	1507
Input Power (W), 4' rail length (1219mm)	49.2	49.2	49.2	49.2
Watts per foot (305mm)	12.4	12.4	12.4	12.4
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | Diffuse, round | 90 CRI | LO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	86	88	90	92
Total Lumens, 4' rail length (1219mm)	1273	1314	1340	1367
Lumens per foot (305mm)	318	328	335	342
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | Diffuse, round | 90 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	106	109	112	114
Total Lumens, 4' rail length (1219mm)	2547	2627	2681	2734
Lumens per foot (305mm)	637	657	670	684
Input Power (W), 4' rail length (1219mm)	24.1	24.1	24.1	24.1
Watts per foot (305mm)	6.1	6.1	6.1	6.1
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

RaceRail® | 107 | Diffuse, round | 90 CRI | HO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	99	102	104	106
Total Lumens, 4' rail length (1219mm)	4839	4991	5093	5195
Lumens per foot (305mm)	1210	1248	1273	1299
Input Power (W), 4' rail length (1219mm)	49.2	49.2	49.2	49.2
Watts per foot (305mm)	12.4	12.4	12.4	12.4
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).