

## IES Report



# WingRail® | 107 | Diffuse | 80 CRI | LO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-D1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	65	67	69	70
Total Lumens, 4' rail length (1219mm)	971	1001	1022	1042
Lumens per foot (305mm)	243	250	255	261
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



**IES Report**



**WingRail® | 107 | Diffuse | 80 CRI | SO**

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-D1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	82	84	86	88
Total Lumens, 4' rail length (1219mm)	1957	2019	2060	2101
Lumens per foot (305mm)	489	505	515	525
Input Power (W), 4' rail length (1219mm)	24.1	24.1	24.1	24.1
Watts per foot (305mm)	6.1	6.1	6.1	6.1
CRI	85	85	85	85

Due to the large number of options in Vode’s product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



**IES Report**



**WingRail® | 107 | Diffuse | 80 CRI | HO**

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-D1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	76	79	80	82
Total Lumens, 4' rail length (1219mm)	3738	3856	3934	4013
Lumens per foot (305mm)	934	964	984	1003
Input Power (W), 4' rail length (1219mm)	49.2	49.2	49.2	49.2
Watts per foot (305mm)	12.4	12.4	12.4	12.4
CRI	85	85	85	85

Due to the large number of options in Vode’s product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# WingRail® | 107 | Diffuse | 90 CRI | LO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-D1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	56	58	59	61
Total Lumens, 4' rail length (1219mm)	837	863	881	899
Lumens per foot (305mm)	209	216	220	225
Input Power (W), 4' rail length (1219mm)	15.0	15.0	15.0	15.0
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# WingRail® | 107 | Diffuse | 90 CRI | SO

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-D1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	71	73	74	76
Total Lumens, 4' rail length (1219mm)	1687	1741	1776	1812
Lumens per foot (305mm)	422	435	444	453
Input Power (W), 4' rail length (1219mm)	24.1	24.1	24.1	24.1
Watts per foot (305mm)	6.1	6.1	6.1	6.1
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



**IES Report**

**WingRail® | 107 | Diffuse | 90 CRI | HO**

107-WG-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-D1-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	66	68	69	71
Total Lumens, 4' rail length (1219mm)	3222	3324	3392	3460
Lumens per foot (305mm)	806	831	848	865
Input Power (W), 4' rail length (1219mm)	49.2	49.2	49.2	49.2
Watts per foot (305mm)	12.4	12.4	12.4	12.4
CRI	96	96	96	96

Due to the large number of options in Vode’s product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).