

## IES Report



# ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	92	95	97	99
Total Lumens, 4' rail length (1219mm)	2821	2911	2970	3029
Lumens per foot (305mm)	705	728	742	757
Lumens per foot UP (305mm)	435	449	458	467
Lumens per foot DOWN (305mm)	270	279	285	290
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	111	114	116	119
Total Lumens, 4' rail length (1219mm)	5643	5821	5940	6059
Lumens per foot (305mm)	1411	1455	1485	1515
Lumens per foot UP (305mm)	870	898	916	934
Lumens per foot DOWN (305mm)	541	558	569	580
Input Power (W), 4' rail length (1219mm)	51.3	51.3	51.3	51.3
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	101	104	106	108
Total Lumens, 4' rail length (1219mm)	10722	11060	11286	11512
Lumens per foot (305mm)	2680	2765	2821	2878
Lumens per foot UP (305mm)	1653	1705	1740	1686
Lumens per foot DOWN (305mm)	1027	1060	1081	1048
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



### ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	79	82	84	87
Total Lumens, 4' rail length (1219mm)	2432	2509	2560	2612
Lumens per foot (305mm)	608	627	640	653
Lumens per foot UP (305mm)	375	387	395	403
Lumens per foot DOWN (305mm)	233	240	245	250
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	95	98	100	104
Total Lumens, 4' rail length (1219mm)	4865	5018	5121	5223
Lumens per foot (305mm)	1216	1255	1280	1306
Lumens per foot UP (305mm)	750	774	790	805
Lumens per foot DOWN (305mm)	466	481	491	500
Input Power (W), 4' rail length (1219mm)	51.3	51.3	51.3	51.3
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric, up | 60° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U1S2-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	87	89	91	95
Total Lumens, 4' rail length (1219mm)	9243	9535	9729	9924
Lumens per foot (305mm)	2311	2384	2432	2481
Lumens per foot UP (305mm)	1425	1470	1500	1454
Lumens per foot DOWN (305mm)	885	913	932	903
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).