

## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 80 CRI | LO

707-Z9-4-48-AW / EW-XX-X-0-Z-LO-35-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	53	55	56	57
Total Lumens, 4' rail length (1219mm)	852	879	897	914
Lumens per foot (305mm)	213	220	224	229
Input Power (W), 4' rail length (1219mm)	16.3	16.3	16.3	16.3
Watts per foot (305mm)	4.1	4.1	4.1	4.1
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 80 CRI | SO

707-Z9-4-48-AW / EW-XX-X-0-Z-SO-35-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	64	66	68	69
Total Lumens, 4' rail length (1219mm)	1703	1757	1793	1829
Lumens per foot (305mm)	426	439	448	457
Input Power (W), 4' rail length (1219mm)	26.7	26.7	26.7	26.7
Watts per foot (305mm)	6.7	6.7	6.7	6.7
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 80 CRI | HO

707-Z9-4-48-AW / EW-XX-X-0-Z-HO-35-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	61	62	64	65
Total Lumens, 4' rail length (1219mm)	3237	3339	3407	3475
Lumens per foot (305mm)	809	835	852	869
Input Power (W), 4' rail length (1219mm)	53.9	53.9	53.9	53.9
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 90 CRI | LO

707-Z9-4-48-AW / EW-XX-X-0-Z-LO-359-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	46	47	48	49
Total Lumens, 4' rail length (1219mm)	734	757	773	788
Lumens per foot (305mm)	184	189	193	197
Input Power (W), 4' rail length (1219mm)	16.25	16.25	16.25	16.25
Watts per foot (305mm)	4.1	4.1	4.1	4.1
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 90 CRI | SO

707-Z9-4-48-AW / EW-XX-X-0-Z-SO-359-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	56	57	59	60
Total Lumens, 4' rail length (1219mm)	1469	1515	1546	1577
Lumens per foot (305mm)	367	379	386	394
Input Power (W), 4' rail length (1219mm)	26.7	26.7	26.7	26.7
Watts per foot (305mm)	6.7	6.7	6.7	6.7
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report

ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 90 CRI | HO

707-Z9-4-48-AW / EW-XX-X-0-Z-HO-359-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	52	54	55	56
Total Lumens, 4' rail length (1219mm)	2790	2878	2937	2996
Lumens per foot (305mm)	698	720	734	749
Input Power (W), 4' rail length (1219mm)	53.9	53.9	53.9	53.9
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).