



**IES Report**  
**ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 80 CRI | LO**  
**707-Z9-4-48-AC / EL-XX-X-0-Z-LO-35-C1-0-AL-0**

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	89	92	94	96
Total Lumens, 4' rail length (1219mm)	1442	1487	1517	1548
Lumens per foot (305mm)	360	372	379	387
Input Power (W), 4' rail length (1219mm)	16.3	16.3	16.3	16.3
Watts per foot (305mm)	4.1	4.1	4.1	4.1
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 80 CRI | SO

707-Z9-4-48-AC / EL-XX-X-0-Z-SO-35-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	109	113	115	117
Total Lumens, 4' rail length (1219mm)	2883	2974	3035	3095
Lumens per foot (305mm)	721	744	759	774
Input Power (W), 4' rail length (1219mm)	26.5	26.5	26.5	26.5
Watts per foot (305mm)	6.7	6.7	6.7	6.7
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



**IES Report**



**ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 80 CRI | HO**

**707-Z9-4-48-AC / EL-XX-X-0-Z-HO-35-C1-0-AL-0**

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	102	105	108	110
Total Lumens, 4' rail length (1219mm)	5478	5651	5766	5881
Lumens per foot (305mm)	1369	1413	1442	1470
Input Power (W), 4' rail length (1219mm)	53.9	53.9	53.9	53.9
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	85	85	85	85

Due to the large number of options in Vode’s product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 90 CRI | LO

707-Z9-4-48-AC / EL-XX-X-0-Z-LO-359-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	77	79	81	84
Total Lumens, 4' rail length (1219mm)	1243	1282	1308	1334
Lumens per foot (305mm)	311	320	327	334
Input Power (W), 4' rail length (1219mm)	16.25	16.25	16.25	16.25
Watts per foot (305mm)	4.1	4.1	4.1	4.1
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 90 CRI | SO

707-Z9-4-48-AC / EL-XX-X-0-Z-SO-359-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	94	97	99	103
Total Lumens, 4' rail length (1219mm)	2485	2564	2616	2669
Lumens per foot (305mm)	621	641	654	667
Input Power (W), 4' rail length (1219mm)	26.5	26.5	26.5	26.5
Watts per foot (305mm)	6.7	6.7	6.7	6.7
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report

ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 90 CRI | HO

707-Z9-4-48-AC / EL-XX-X-0-Z-HO-359-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	88	91	93	97
Total Lumens, 4' rail length (1219mm)	4722	4871	4971	5070
Lumens per foot (305mm)	1181	1218	1243	1268
Input Power (W), 4' rail length (1219mm)	53.9	53.9	53.9	53.9
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).