

IES Report



DoubleBox™ | 107 | Wide Batwing, up | 85° Asymmetric, down | 80 CRI | LO

107-DB-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-G1A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	80	82	84	84
Total Lumens, 4' rail length (1219mm)	2192	2261	2307	2307
Lumens per foot (305mm)	548	565	577	577
Lumens per foot UP (305mm)	371	383	391	391
Lumens per foot DOWN (305mm)	177	182	186	186
Input Power (W), 4' rail length (1219mm)	27.6	27.6	27.6	27.6
Watts per foot (305mm)	6.9	6.9	6.9	6.9
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



DoubleBox™ | 107 | Wide Batwing, up | 85° Asymmetric, down | 80 CRI | SO

107-DB-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-G1A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	92	95	97	97
Total Lumens, 4' rail length (1219mm)	4384	4522	4614	4614
Lumens per foot (305mm)	1096	1131	1154	1154
Lumens per foot UP (305mm)	743	766	782	782
Lumens per foot DOWN (305mm)	353	364	372	372
Input Power (W), 4' rail length (1219mm)	47.8	47.8	47.8	47.8
Watts per foot (305mm)	12.0	12.0	12.0	12.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



DoubleBox™ | 107 | Wide Batwing, up | 85° Asymmetric, down | 80 CRI | HO

107-DB-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-G1A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	85	88	90	90
Total Lumens, 4' rail length (1219mm)	8329	8592	8768	8768
Lumens per foot (305mm)	2082	2148	2192	2192
Lumens per foot UP (305mm)	1411	1456	1485	1485
Lumens per foot DOWN (305mm)	671	692	706	706
Input Power (W), 4' rail length (1219mm)	98.1	98.1	98.1	98.1
Watts per foot (305mm)	24.6	24.6	24.6	24.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



DoubleBox™ | 107 | Wide Batwing, up | 85° Asymmetric, down | 90 CRI | LO

107-DB-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-G1A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	69	71	73	73
Total Lumens, 4' rail length (1219mm)	1890	1949	1989	2009
Lumens per foot (305mm)	472	487	497	502
Lumens per foot UP (305mm)	320	330	337	340
Lumens per foot DOWN (305mm)	152	157	160	162
Input Power (W), 4' rail length (1219mm)	27.6	27.6	27.6	27.6
Watts per foot (305mm)	6.9	6.9	6.9	6.9
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



DoubleBox™ | 107 | Wide Batwing, up | 85° Asymmetric, down | 90 CRI | SO

107-DB-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-G1A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	80	82	84	85
Total Lumens, 4' rail length (1219mm)	3779	3898	3978	4018
Lumens per foot (305mm)	945	975	995	1004
Lumens per foot UP (305mm)	640	660	674	681
Lumens per foot DOWN (305mm)	304	314	320	324
Input Power (W), 4' rail length (1219mm)	47.8	47.8	47.8	47.8
Watts per foot (305mm)	12.0	12.0	12.0	12.0
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

DoubleBox™ | 107 | Wide Batwing, up | 85° Asymmetric, down | 90 CRI | HO

107-DB-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-G1A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	74	76	78	78
Total Lumens, 4' rail length (1219mm)	7180	7407	7558	7634
Lumens per foot (305mm)	1795	1852	1890	1908
Lumens per foot UP (305mm)	1216	1255	1281	1293
Lumens per foot DOWN (305mm)	578	597	609	615
Input Power (W), 4' rail length (1219mm)	98.1	98.1	98.1	98.1
Watts per foot (305mm)	24.6	24.6	24.6	24.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).