



8165 E Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Report No: L121911519TM30

Date: 1/8/2020






TM-30-15 REPORT


Report No:	L121911519TM30
Prepared For:	Vode Lighting 21684 8th Street East, Suite 700, Sonoma, CA 95476
Model Number:	107-WG-48-Z-SO-359-WB-AL
Testing Lab:	Light Laboratory Inc.
Reference report No:	L121911519
Remark:	This report is based on the data from Light Laboratory Inc. report L121911519

Results Summary

Metric	Result	Notes
R_f	90	IES TM-30-15 Fidelity Index
R_g	99	IES TM-30-15 Gamut Index
CIE R_a	94	CIE Test Color Method General Index
R_9	56	CIE Test Color Method Sample Nine Score
$R_{f,skin}$	94	Average of CES15 and CES18 (skin)
CCT	3323	Correlated Color Temperature
D_{uv}	-0.0007	Distance from the blackbody locus
x	0.4149	CIE 1931 chromaticity coordinate
y	0.3937	CIE 1931 chromaticity coordinate
u	0.2407	CIE 1960 chromaticity coordinate
v	0.3426	CIE 1960 chromaticity coordinate
u'	0.2407	CIE 1976 chromaticity coordinate
v'	0.5139	CIE 1976 chromaticity coordinate


*All Results in accordance to IES TM-30-15: IES Method for Evaluating Light Source Color Rendition





Hue Bin	R_f	Graphic shifts (%)	
		Chroma	Hue
1	88	-5%	1%
2	92	-3%	2%
3	93	-1%	2%
4	94	-3%	-1%
5	91	-5%	1%
6	96	0%	1%
7	92	-3%	2%
8	96	1%	2%
9	91	0%	6%
10	87	0%	8%
11	86	4%	7%
12	87	7%	-2%
13	89	2%	-7%
14	84	3%	-11%
15	85	-2%	-7%
16	84	-2%	-9%

Hue Angle Bin vs. Fidelity Index



Hue Angle Bin vs. Change of Chroma

