



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	105	108	110	110
Total Lumens, 4' rail length (1219mm)	3100	3198	3263	3263
Lumens per foot (305mm)	775	800	816	816
Lumens per foot UP (305mm)	300	310	316	316
Lumens per foot DOWN (305mm)	475	490	500	500
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	119	123	125	125
Total Lumens, 4' rail length (1219mm)	6201	6396	6527	6527
Lumens per foot (305mm)	1550	1599	1632	1632
Lumens per foot UP (305mm)	600	619	632	632
Lumens per foot DOWN (305mm)	950	980	1000	1000
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	110	113	116	116
Total Lumens, 4' rail length (1219mm)	11781	12153	12401	12401
Lumens per foot (305mm)	2945	3038	3100	3100
Lumens per foot UP (305mm)	1141	1177	1201	1201
Lumens per foot DOWN (305mm)	1805	1862	1900	1900
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	90	93	95	99
Total Lumens, 4' rail length (1219mm)	2673	2757	2813	2841
Lumens per foot (305mm)	668	689	703	710
Lumens per foot UP (305mm)	259	267	272	275
Lumens per foot DOWN (305mm)	409	422	431	435
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	103	106	108	112
Total Lumens, 4' rail length (1219mm)	5345	5514	5627	5683
Lumens per foot (305mm)	1336	1379	1407	1421
Lumens per foot UP (305mm)	518	534	545	550
Lumens per foot DOWN (305mm)	819	845	862	871
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 80° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2S7-0-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	95	98	100	104
Total Lumens, 4' rail length (1219mm)	10156	10477	10691	10797
Lumens per foot (305mm)	2539	2619	2673	2699
Lumens per foot UP (305mm)	983	1014	1035	1045
Lumens per foot DOWN (305mm)	1556	1605	1638	1654
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27	27	27	27
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.