

## IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, up | 85° Asymmetric , down | 80 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-35-U2A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	114	118	120	120
Total Lumens, 4' rail length (1219mm)	3380	3487	3558	3558
Lumens per foot (305mm)	845	872	889	889
Lumens per foot UP (305mm)	503	519	529	529
Lumens per foot DOWN (305mm)	342	353	360	360
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, up | 85° Asymmetric , down | 80 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-35-U2A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	130	134	137	137
Total Lumens, 4' rail length (1219mm)	6760	6973	7115	7115
Lumens per foot (305mm)	1690	1743	1779	1779
Lumens per foot UP (305mm)	1006	1037	1058	1058
Lumens per foot DOWN (305mm)	684	706	720	720
Input Power (W), 4' rail length (1219mm)	52.2	52.2	52.2	52.2
Watts per foot (305mm)	13.1	13.1	13.1	13.1
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, up | 85° Asymmetric , down | 80 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-35-U2A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	120	124	126	126
Total Lumens, 4' rail length (1219mm)	12843	13249	13519	13519
Lumens per foot (305mm)	3211	3312	3380	3380
Lumens per foot UP (305mm)	1911	1971	2011	2011
Lumens per foot DOWN (305mm)	1300	1341	1369	1369
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27.0	27.0	27.0	27.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, up | 85° Asymmetric , down | 90 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-359-U2A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	98	101	103	107
Total Lumens, 4' rail length (1219mm)	2914	3006	3067	3098
Lumens per foot (305mm)	728	751	767	774
Lumens per foot UP (305mm)	433	447	456	461
Lumens per foot DOWN (305mm)	295	304	311	314
Input Power (W), 4' rail length (1219mm)	29.8	29.8	29.8	29.8
Watts per foot (305mm)	7.5	7.5	7.5	7.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report



ZipThree® | 707 | Symmetric with EdgeGlow™, up | 85° Asymmetric , down | 90 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-359-U2A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	111	114	117	122
Total Lumens, 4' rail length (1219mm)	5827	6011	6134	6195
Lumens per foot (305mm)	1457	1503	1534	1549
Lumens per foot UP (305mm)	867	894	912	922
Lumens per foot DOWN (305mm)	590	609	621	627
Input Power (W), 4' rail length (1219mm)	52.8	52.8	52.8	52.8
Watts per foot (305mm)	13.3	13.3	13.3	13.3
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).



## IES Report

ZipThree® | 707 | Symmetric with EdgeGlow™, up | 85° Asymmetric , down | 90 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-359-U2A1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	103	107	109	113
Total Lumens, 4' rail length (1219mm)	11072	11422	11655	11771
Lumens per foot (305mm)	2768	2855	2914	2943
Lumens per foot UP (305mm)	1647	1699	1734	1663
Lumens per foot DOWN (305mm)	1121	1156	1180	1132
Input Power (W), 4' rail length (1219mm)	107.7	107.7	107.7	107.7
Watts per foot (305mm)	27	27	27	27
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](http://vode.com).