

## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 80 CRI | LO

707-Z9-4-48-AW / EW-XX-X-0-Z-LO-35-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	60	62	63	63
Total Lumens, 4' rail length (1219mm)	885	913	932	932
Lumens per foot (305mm)	221	228	233	233
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 80 CRI | SO

707-Z9-4-48-AW / EW-XX-X-0-Z-SO-35-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	68	70	71	71
Total Lumens, 4' rail length (1219mm)	1771	1827	1864	1864
Lumens per foot (305mm)	443	457	466	466
Input Power (W), 4' rail length (1219mm)	26.4	26.4	26.4	26.4
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 80 CRI | HO

707-Z9-4-48-AW / EW-XX-X-0-Z-HO-35-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	63	65	66	66
Total Lumens, 4' rail length (1219mm)	3365	3471	3542	3542
Lumens per foot (305mm)	841	868	885	885
Input Power (W), 4' rail length (1219mm)	53.7	53.7	53.7	53.7
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 90 CRI | LO

707-Z9-4-48-AW / EW-XX-X-0-Z-LO-359-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	52	53	54	55
Total Lumens, 4' rail length (1219mm)	763	787	803	812
Lumens per foot (305mm)	191	197	201	203
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



**ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 90 CRI | SO**

**707-Z9-4-48-AW / EW-XX-X-0-Z-SO-359-C1-0-AL-0**

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	58	60	61	62
Total Lumens, 4' rail length (1219mm)	1527	1575	1607	1623
Lumens per foot (305mm)	382	394	402	406
Input Power (W), 4' rail length (1219mm)	26.5	26.5	26.5	26.5
Watts per foot (305mm)	6.7	6.7	6.7	6.7
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report

ZipWave® | 707 | Clear with EdgeSoft™, fixture in cove | 90 CRI | HO

707-Z9-4-48-AW / EW-XX-X-0-Z-HO-359-C1-0-AL-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	54	56	57	58
Total Lumens, 4' rail length (1219mm)	2901	2992	3053	3084
Lumens per foot (305mm)	725	748	763	771
Input Power (W), 4' rail length (1219mm)	53.7	53.7	53.7	53.7
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).