

IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 80 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-35-A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	66	68	69	69
Total Lumens, 4' rail length (1219mm)	970	1001	1022	1022
Lumens per foot (305mm)	243	250	255	255
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 80 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-35-A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	75	77	79	79
Total Lumens, 4' rail length (1219mm)	1941	2002	2043	2043
Lumens per foot (305mm)	485	501	511	511
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 80 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-35-A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	69	71	73	73
Total Lumens, 4' rail length (1219mm)	3688	3804	3882	3882
Lumens per foot (305mm)	922	951	970	970
Input Power (W), 4' rail length (1219mm)	53.8	53.8	53.8	53.8
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 90 CRI | LO

707-Z3-4-48-XX-XX-X-0-Z-LO-359-A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	57	58	60	62
Total Lumens, 4' rail length (1219mm)	837	863	881	889
Lumens per foot (305mm)	209	216	220	222
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | 707 | 85° Asymmetric , downlight only | 90 CRI | SO

707-Z3-4-48-XX-XX-X-0-Z-SO-359-A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	65	67	68	71
Total Lumens, 4' rail length (1219mm)	1673	1726	1761	1779
Lumens per foot (305mm)	418	432	440	445
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

ZipThree® | 707 | 85° Asymmetric , downlight only | 90 CRI | HO

707-Z3-4-48-XX-XX-X-0-Z-HO-359-A1-X-BL-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	60	61	63	66
Total Lumens, 4' rail length (1219mm)	3179	3279	3346	3380
Lumens per foot (305mm)	795	820	837	845
Input Power (W), 4' rail length (1219mm)	53.8	53.8	53.8	53.8
Watts per foot (305mm)	13.5	13.5	13.5	13.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).