





Adaptive architectural lighting systems



Spec Guide

ZipTwo® | Square 3555 | 707

Direct lighting for open office and ambient applications.



Square 3555, Side Diffuse, white

Benefits & Features

Minimal Profile, Robust Design

Square profile. 1.38" (35mm) x 2.13" (54mm).

Superior Light Quality & Performance


Output up to 1517 lm/ft (4976 lm/m) (HO), 155 lm/W (SO). 80 or 90 CRI & tunable white (2200K-5000K) available.

Versatile Mounting, Easy Installation

Magnet with tape-on metal strip or low profile clip allow for mounting to almost any surface or T-Bar ceiling.

Extensive Optics

Options of Diffuse, Critical Edge, and Side Diffuse give designers the power to create and design their space using one product.



Square 3555, Diffuse, white



Square 3555, Side Diffuse, Black

Build Your Specification

707-Z2	SL				0 ▶▶
--------	----	--	--	--	------

System & Rail Type	System Type	System Length	Rail Length	Mounting	Arm/Cord Length
707-Z2 ZipTwo	SL Standard Linear	Specify overall system length in ft/in or M/mm. <i>Corners and Shapes Available. See Corners and Shapes Guide for more details.</i>	24 24" (610mm) 36 36" (914mm) 48 48" (1219mm) 60 60" (1524mm) 72 72" (1829mm) 96 96" (2438mm) 108 108" (2743mm) 120 120" (3048mm) 132 132" (3352mm) 144 144" (3658mm) ZZ Other rail length or layout (please specify) <i>See Rail Length Chart for more details</i>	C Clip CM Clip with Micro J-Box T Magnet with Tape-On Metal Strip T1 9/16" T-Bar Clip, low profile T2 15/16" T-Bar Clip, low profile T3 15/16" T-Bar Clip, medium profile T4 15/16" T-Bar Clip, concealed T5 9/16" T-Bar Clip, medium profile T6 Slotted T-Bar Clip T7 Dimensional T-Bar Clip SC Strut Channel Clip DM Armstrong DynaMax ZZ Other (please specify)	0 None

▶▶				Z ▶▶
----	--	--	--	------

Power Location	Power Type	Voltage	Emergency Power	LED Type
Remote Power	Flexible 1 to 1 Power	1 120v 2 120v-277v X Not Yet Specified	0 No Emergency Power ZZ Emergency Power (<i>specify requirements</i>)	Z Zipper Board™
RP25 25' (7.62m) Wire Harness RP50 50' (15.24m) Wire Harness RP75 75' (22.86m) Wire Harness RP100 100' (30.48m) Wire Harness	AE eldoLED 0-10v, 1.0% Dimming AT eldoLED 0-10v, 0.1% Dimming AD eldoLED DALI, 0.1% Dimming AX eldoLED DMX, 100-0% Dimming AH Hi-lume 1% EcoSystem, Soft On / Fade to Black Technology, LDE1 AH2 Hi-lume 1% 2-wire LTEA2W (120V forward phase only) Optimized Power AEO eldoLED 0-10v, 1.0% Dimming ATO eldoLED 0-10v, 0.1% Dimming ADO eldoLED DALI, 0.1% Dimming AXO eldoLED DMX, 100-0% Dimming ZZ Other (please specify) <i>*See Power Guide for driver features & limitations.</i>			

▶▶			
----	--	--	--

Lumen Output	Color Temperature ³	Optics	Sensors
LO Low Output SO Standard Output HO High Output* ZZ Other (please specify) <i>See IES Files page for details.</i> <i>*See Power Guide for driver features & limitations.</i>	80+ CRI 27 2700K 30 3000K 35 3500K 40 4000K 90+ CRI 279 2700K 309 3000K 359 3500K 409 4000K ZZ Tunable White Available See Guide for details	J6 Square 3555, Diffuse ¹ J9 Square 3555, Side Diffuse JA Square 3555, Single Side Diffuse	0 None ZZ Other (please specify) ²

▶▶	
----	--

Finish	Options
WH White BL Black	0 None 9 9' 18/3 Cord and Plug CP Contact factory for Chicago Plenum

NOTES & LIMITATIONS

¹ Square 3555, Diffuse is only available in White Finish (WH).² Sensors available. Contact [Vode](#) for more information.³ RGBW available. Contact [Vode](#) for more information.5 Year Limited Warranty. See full Vode warranty description [here](#) or at [vode.com](#).

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA.



Applications

General Interior and Open Office



Square 3555, Diffuse



Square 3555, Side Diffuse



Square 3555, Side Diffuse

Structure

Rail Lengths	24" (610mm) - 144" (3658mm) See Rail Length Chart for more details.
Rail Dimensions	1.38" (35mm) x 2.13" (54mm). See dimensions section for details.
Construction	Extruded and machined 6063 aluminum.
Mounting	Clip, Clip with Micro J-Box, Magnet with Tape-On Metal Strip, T-Bar Clips for most grid/panel construction, Strut Channel Clip.
Run Length	24" (610mm) minimum. Rail lengths may be installed end-to-end to any length.
Operating Temperature	32°F to 104°F (0°C to 40°C).
Humidity	0-95%, non-condensing. Suitable for damp locations.
System Weight	0.34lbs per ft (0.15kg per 305mm). Power supply and housing not included.

Materials


LED Board Construction	Aluminum core PCB, black LCP connectors, RoHS compliant.
Lens	High-impact extruded acrylic glass (PMMA).
Power Cable	Ø3mm, 33/2 AWG, Plenum (CMP) rated semi-rigid PVC or FEP, flame tested UL-910, red list free.
Cable Connectors	Unfilled black nylon, rated UL 94 V-0, halogen free, PVC or FEP overmold, RoHS compliant, red list free.
Remote Linear Power Housing (RLP)	20.7" x 2.375" x 2.53", 0.054" formed Galvanized Steel.
Remote Brick Power Housing (RBP)	4.32" x 3.37" x .078" Galvanized Steel mounting plate.

Power and Controls

Power Type	Class 2 (<60v output) constant current driver
Dimming Controls	Dimming (0.1%, 1%), 0-10v, DALI, DMX, Lutron Hi-lume 1% are available. See Power Guide for details.
Input Voltage	120v - 277v, 50/60hz
Power Location	Remote power. Maximum remote distance up to 100' (30.5m) depending on driver selection. See Power Guide for details.


Remote power is locating the power supply away from the fixture. Remote power comes in two housing styles: brick style and linear style. Consult [Power Guide](#) to determine which type you will receive.

Remote Brick Power Housing




Supplied for some remote power applications. One remote power supply housing is supplied for each rail. Provided driver mounting plate fits standard 4" metal, square J-Boxes with a minimum volume of 21 in³ (J-Box not provided). See [Tech Sheet](#) for details.

Remote Linear Power Housing



One remote power supply housing is supplied with each power supply. All Vode linear remote drivers come in a 0.054" (0.8mm) formed galvanized steel power supply housing with five (5) knockouts: (4) 1-1/8", (1) 7/8" and (1) 9/16". Accommodates standard linear power supplies. See [Tech Sheet](#) for details.

Wire Harness




Wire harness connects driver to rail. Wire harness is 25' (7.6m) with micro fit molex connectors for quick and easy installation. Multiple harnesses can be combined for a total length of up to 100' (30.5m). See [Tech Sheet](#) for details.

Power and Controls

Flexible 1 to 1 power


For Flexible 1 to 1 Power, Vode supplies one single output driver per fixture, allowing each fixture to be controlled independently. Direct/Indirect fixtures are supplied with two single output drivers, allowing the direct and indirect lighting to be controlled independently. Consult [Power Guide](#) to determine which type you will receive.



Optimized Power

To optimize power, Vode configures specifications with drivers that have 2 or 4 outputs. Depending on system configurations and power requirements, up to 4 fixtures can be powered from a 4-output driver. Consult [Power Guide](#) to determine which type you will receive.

IMPORTANT: Each fixture will still require individual wire harnesses, as shown below.




Note: Drawings not to scale, for reference only.

Power and Controls


Wire Harness

Low voltage wire harness connects driver to rail. Wire harness is 25' (7.6m) 18/2 AWG stranded wire with provided micro fit molex connectors on either end for quick and easy installation. Multiple harnesses can be combined for a total length of up to 100' (30.5m). Refer to Vode Power Guide for max remote distance based on power selection. Consult [Power Guide](#) to determine which type you will receive.




Note: Drawings not to scale, for reference only.

Dimensions




Layout




Corner and Shapes Available (Square, Rectangle, L-Shape, U-Shape, ZigZag)

[See Guide](#) for details


Mounting Options




Clip (C)




Clip with Micro J-Box (CM)




Magnet with Tape-On Metal Strip (T)




9/16" T-Bar Clip, low profile (T1)




15/16" T-Bar Clip, low profile (T2)




15/16" T-Bar Clip, medium profile (T3)




15/16" T-Bar Clip, concealed (T4)




9/16" T-Bar Clip, medium profile (T5)




Slotted T-Bar Clip (T6)



Dimensional T-Bar Clip (T7)



Strut Channel Clip (SC)




Armstrong DynaMax (DM)

See [ZipTwo Clip Guide](#) to check compatibility.

Performance | Zipper LED

Zipper Board has 72 diodes per foot (305mm). Testing based on a 4' rail section. Lumen measurement complies with IES-LM-79-08 testing procedures.

Square 3555, Diffuse, white finish (J6-WH)



L80 >60,000 hours

	80 CRI (80min., 84 avg.)				90 CRI (90min., 96 avg.)			
Low Output (LO)	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	130	134	136	136	112	115	118	119
Lumens per foot (305mm)	480	495	506	506	414	427	436	440
Watts per foot (305mm)	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8


Standard Output (SO)

Efficacy - Lumens per Watt	148	152	155	155	127	131	134	135
Lumens per foot (305mm)	961	991	1011	1011	828	854	872	880
Watts per foot (305mm)	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6

High Output (HO)

Efficacy - Lumens per Watt	146	151	154	154	126	130	133	134
Lumens per foot (305mm)	1441	1486	1517	1517	1242	1281	1308	1321
Watts per foot (305mm)	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9

Square 3555, Side Diffuse, white finish (J9-WH)



L80 >60,000 hours

	80 CRI (80min., 84 avg.)				90 CRI (90min., 96 avg.)			
Low Output (LO)	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	115	119	121	121	99	103	105	106
Lumens per foot (305mm)	427	440	449	449	368	380	387	391
Watts per foot (305mm)	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8

Standard Output (SO)

Efficacy - Lumens per Watt	131	135	138	138	113	117	119	120
Lumens per foot (305mm)	854	881	899	899	736	759	775	783
Watts per foot (305mm)	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6


High Output (HO)

Efficacy - Lumens per Watt	130	134	137	137	112	116	118	119
Lumens per foot (305mm)	1281	1321	1348	1348	1104	1139	1162	1174
Watts per foot (305mm)	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9

Performance | Zipper LED

Zipper Board has 72 diodes per foot (305mm). Testing based on a 4' rail section. Lumen measurement complies with IES-LM-79-08 testing procedures.

Square 3555, Single Side Diffuse, white finish (JA-WH)



L80 >60,000 hours

	80 CRI (80min., 84 avg.)				90 CRI (90min., 96 avg.)			
	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Low Output (LO)								
Efficacy - Lumens per Watt	93	96	98	98	80	83	85	86
Lumens per foot (305mm)	345	356	363	363	298	307	313	316
Watts per foot (305mm)	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8


Standard Output (SO)

Efficacy - Lumens per Watt	106	110	112	112	91	94	96	97
Lumens per foot (305mm)	691	712	727	727	595	614	627	633
Watts per foot (305mm)	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6

High Output (HO)

Efficacy - Lumens per Watt	105	109	111	111	91	94	96	97
Lumens per foot (305mm)	1036	1068	1090	1090	893	921	940	949
Watts per foot (305mm)	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9

Square 3555, Side Diffuse, black finish (J9-BL)



L80 >60,000 hours

	80 CRI (80min., 84 avg.)				90 CRI (90min., 96 avg.)			
	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Low Output (LO)								
Efficacy - Lumens per Watt	112	115	117	117	96	99	101	102
Lumens per foot (305mm)	414	427	435	435	356	368	375	379
Watts per foot (305mm)	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8

Standard Output (SO)

Efficacy - Lumens per Watt	127	131	134	134	110	113	115	116
Lumens per foot (305mm)	827	853	871	871	713	735	750	758
Watts per foot (305mm)	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6


High Output (HO)

Efficacy - Lumens per Watt	126	130	133	133	109	112	114	115
Lumens per foot (305mm)	1241	1280	1306	1306	1069	1103	1126	1137
Watts per foot (305mm)	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9

Performance | Zipper LED

Zipper Board has 72 diodes per foot (305mm). Testing based on a 4' rail section. Lumen measurement complies with IES-LM-79-08 testing procedures.

Square 3555, Single Side Diffuse, black finish (JA-BL)



L80 >60,000 hours

	80 CRI (80min., 84 avg.)				90 CRI (90min., 96 avg.)			
	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Low Output (LO)								
Efficacy - Lumens per Watt	88	91	93	93	76	78	80	81
Lumens per foot (305mm)	325	336	343	343	281	289	295	298
Watts per foot (305mm)	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8
Standard Output (SO)								
Efficacy - Lumens per Watt	100	103	105	105	86	89	91	92
Lumens per foot (305mm)	651	671	685	685	561	579	591	597
Watts per foot (305mm)	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6
High Output (HO)								
Efficacy - Lumens per Watt	99	102	104	104	86	88	90	91
Lumens per foot (305mm)	976	1007	1028	1028	842	868	886	895
Watts per foot (305mm)	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9