

## Spec Guide

# ZipWave™ | Wall Cove | 707

Wall cove lighting system for wall wash and grazing applications.



ZipWave: indirect cove light.

## Benefits & Features

### Perfect Light Distribution

Optimized distribution, no tuning necessary. Designed for Armstrong® AXIOM® Indirect Light Coves and site-built coves.

### Superior Light Quality with High Efficiency

Output up to 1666 lm/ft (5465 lm/m) (HO), 132 lm/W (SO). 80 or 90 CRI & tunable white (2200K-6500K) available.

### Easy Installation, Minimal Electrical Circuits

Simply drops into cove with no tools required. Plug & play integral power and control circuits provided. Up to 533' can be powered with one 277v feed.

### Better Beam Performance

EdgeSoft™ lens for soft distribution down wall surface without reflected diode image.



Quick Connect Cables.



Fixture installed in AXIOM Classic-Edge cove

## Build Your Specification

707-Z9	SL				0
<b>System &amp; Rail Type</b>	<b>System Type</b>	<b>System Length</b>	<b>Rail Length</b>	<b>Mounting</b>	<b>Arm/Cord Length</b>
707-Z9 ZipWave	SL Standard Linear	Specify overall system length in ft/in or M/mm.	<b>24</b> 24" (610mm) <b>36</b> 36" (914mm) <b>48</b> 48" (1219mm) <b>60</b> 60" (1524mm) <b>72</b> 72" (1829mm) <b>96</b> 96" (2438mm) <b>ZZ</b> Other rail length or layout (please specify)	<b>EW</b> Engineered Wall Cove <b>AW</b> Armstrong® Wall Cove <b>ZZ</b> Other (please specify)	<b>0</b> None

IP				Z
<b>Power Location</b>	<b>Power Type</b>	<b>Voltage</b>	<b>Emergency Power</b>	<b>LED Type</b>
IP Integral Power	<b>Integral Power*</b> <b>AE</b> eldoLED 0-10v, 1.0% Dimming <b>AT</b> eldoLED 0-10v, 0.1% Dimming <b>AD</b> eldoLED DALI, 0.1% Dimming <b>AX</b> eldoLED DMX, 100-0% Dimming <b>AH</b> Hi-lume 1% EcoSystem, Soft On / Fade to Black Technology, LDE1 <b>AH2</b> Hi-lume 1% 2-wire LTEA2W (120V forward phase only) <b>ZZ</b> Other (please specify)	<b>1</b> 120v <b>2</b> 120v-277v <b>X</b> Not Yet Specified	<b>0</b> No Emergency Power <b>ZZ</b> Emergency Power (specify requirements)	<b>Z</b> Zipper Board™

\*See [Power Guide](#) for driver features & limitations.

		C1		AL	0
<b>Lumen Output</b>	<b>Color Temperature</b>	<b>Optics</b>	<b>Sensors</b>	<b>Finish</b>	<b>Options</b>
<b>LO</b> Low Output <b>SO</b> Standard Output <b>HO</b> High Output* <b>ZZ</b> Other (please specify) See <a href="#">IES Files</a> page for details. *See <a href="#">Power Guide</a> for driver features & limitations.	<b>80+ CRI</b> <b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K  <b>90+ CRI</b> <b>279</b> 2700K <b>309</b> 3000K <b>359</b> 3500K <b>409</b> 4000K <b>ZZ</b> Other (please specify)	<b>C1</b> Clear with EdgeSoft™	<b>0</b> None <b>ZZ</b> Sensor (specify requirements)	<b>AL</b> Clear Anodized	<b>0</b> None



## Jumper Cables Sold Separately:

Vode offers a 2' (Part Number: PWH-707-Z9-24-MF-RLF-WJ) or 6' (Part Number: PWH-707-Z9-72-MF-RLF-WJ) jumper for corner installations. Please indicate on your order the type and quantity required.

5 Year Limited Warranty. See full Vode warranty description [here](#) or at [vode.com](#).

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA.



Applications



Vode supplies ZipWave cove product only. Armstrong cove products supplied by Armstrong.

Armstrong® AXIOM® Indirect Light Cove, Ceiling-to-Wall


ZipWave perfectly integrates into Armstrong AXIOM Indirect Light Coves and Field Coves to provide seamless light quality in office, hospitality, civic and retail applications.

Engineered or Site-built Wall Cove

ZipWave can easily be placed into a wide variety of engineered commercial lighting coves and site-built coves. Up to 533 feet (162m) of Low Output fixtures can be powered by a single 277v power feed.



Corner Layout



**Jumper Cables Sold Separately:**  
Vode offers a 2' (Part Number: PWH-707-Z9-24-MF-RLF-WJ) or 6' (Part Number: PWH-707-Z9-72-MF-RLF-WJ) jumper for corner installations. Please indicate on your order the type and quantity required.


Structure

Rail Lengths	24" (610mm), 36" (914mm), 48" (1219mm), 60" (1524mm), 72" (1829mm), 96" (2438mm).
Rail Dimensions	1.6" (41mm) x 3.8" (97mm).
Construction	Extruded and machined 6063 aluminum.
Mounting	Integral power housing compatible with Armstrong AXIOM Indirect Light Coves, and Field Coves, engineered and site-built coves.
System Run Length	24" (610mm) minimum. Rail lengths may be installed up to 533' (162m) on a single power feed.
Operating Temperature	32°F to 104°F (0°C to 40°C).
Humidity	0-95%, non-condensing.
Weight	1.1 lbs per ft (0.50kg per 305mm). <i>Weight will vary slightly due to driver selection.</i>


Materials

LED Board Construction	Aluminum core PCB, black LCP connectors, RoHS compliant.
Lens	High-impact extruded acrylic glass (PMMA).
Cable	Ø8mm, 6 wire, UL21388, Mylar Black with UV resistant PVC jacket.

## Dimensions



## Layout



## System Length per Power Feed


### 24" - 72" Rail Lengths

Input Voltage	Output		
	LO	SO	HO
120	267' (81m)	134' (40m)	67' (20m)
277	615' (187m)	308' (93m)	154' (46m)

### 96" Rail Lengths (any system that contains at least one 96" rail)

Input Voltage	Output		
	LO	SO	HO
120	209' (63m)	107' (32m)	54' (16m)
277	481' (146m)	247' (75m)	124' (37m)

## Quick Connect Cables




## Power and Controls

Power Type	Class 2 (<60v output) constant current driver.
Controls	Dimming (0.1%, 1%), 0-10v, DALI, DMX, Lutron Hi-lume 1% are available. See <a href="#">Power Guide</a> for details.
Input Voltage	120v - 277v, 50/60hz.
Power Location	Integral power only. Power cable is 27" (686mm) with 7.875" (200mm) male-male jumper.

## Performance | Zipper LED

Zipper Board has 72 diodes per foot (305mm). Testing based on a 4' rail section. Lumen measurement complies with IES-LM-79-08 testing procedures.

### Clear with EdgeSoft (C1), fixture only



L80 >60,000 hours

#### 80 CRI (80min., 84 avg.)

#### 90 CRI (90min., 96 avg.)

Low Output (LO)	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	101	104	106	108	87	90	91	95
Lumens per foot (305mm)	407	420	429	437	351	362	370	377
Watts per foot (305mm)	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1


#### Standard Output (SO)

Efficacy - Lumens per Watt	123	127	129	132	106	109	112	116
Lumens per foot (305mm)	815	840	858	875	702	724	739	754
Watts per foot (305mm)	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7

#### High Output (HO)

Efficacy - Lumens per Watt	116	119	122	124	100	103	105	109
Lumens per foot (305mm)	1551	1600	1633	1666	1337	1380	1408	1436
Watts per foot (305mm)	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5

### Clear with EdgeSoft (C1), in cove<sup>1</sup>



L80 >60,000 hours

#### 80 CRI (80min., 84 avg.)

#### 90 CRI (90min., 96 avg.)

Low Output (LO)	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	53	55	56	57	46	47	48	49
Lumens per foot (305mm)	213	220	224	229	184	189	193	197
Watts per foot (305mm)	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1

#### Standard Output (SO)

Efficacy - Lumens per Watt	64	66	68	69	56	57	59	60
Lumens per foot (305mm)	426	439	448	457	367	379	386	394
Watts per foot (305mm)	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7

#### High Output (HO)

Efficacy - Lumens per Watt	61	62	64	65	52	54	55	56
Lumens per foot (305mm)	809	835	852	869	698	720	734	749
Watts per foot (305mm)	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5

#### NOTES & LIMITATIONS

<sup>1</sup>Based on testing 4' rail section placed inside 4' cove section of an Armstrong AXIOM Indirect Light Cove, classic profile. Lumen measurement complies with IES-LM-79-08 testing procedures.

© 2018 Vode Lighting LLC. All rights reserved.

The Vode logo and Vode, ZipWave and Zipper Board names are either registered trademarks or trademarks of Vode Lighting LLC in the United States and/or other countries. All other brand or product names are trademarks or registered trademarks of their respective owners. Due to ongoing innovation, specifications may change without notice.