



Adaptive architectural lighting systems



Spec Guide

ZipTwo® | Square 3535/30 | Ceiling Cable | 707

Direct or indirect lighting for wall wash and ceiling wash applications.



Square 3535/30, Soft Wash, white

Benefits & Features

Minimal Profile, Robust Design

Asymmetric profile. 1.38" (35mm) x 1.42" (36mm) / 30°.

Superior Light Quality & Performance


Output up to 1068 lm/ft (3503 lm/m) (HO), 109 lm/W HO. 80 or 90 CRI & tunable white (2200K-5000K) available.

Adaptive Power Body


Full range dimming power for all protocols. Integral or remote power available. Remote power available up to 100' (30.5m) away.

Discrete Wall Washer

Asymmetric lens with Soft Wash minimizes glare while subtly casting light on a surface.



Small Round Canopy



Integral Power

Build Your Specification

707-Z2	S			CC	0	»
--------	---	--	--	----	---	---

System & Rail Type	System Type	System Length	Rail Length	Mounting	Arm/Cord Length
707-Z2 ZipTwo	S Suspended	Specify overall system length in ft/in or M/mm. <i>Corners and Shapes Available. See Corners and Shapes Guide for more details.</i>	24 24" (610mm) 36 36" (914mm) 48 48" (1219mm) 60 60" (1524mm) 72 72" (1829mm) 96 96" (2438mm) 108 108" (2743 mm) 120 120" (3048 mm) 132 132" (3352 mm) 144 144" (3658 mm) ZZ Other rail length or layout (please specify)	CC Ceiling Cable	48 48" cord (1219mm) 96 96" cord (2438mm) ZZ Other (please specify)
See Rail Length Chart for more details					

»			0	Z	»
---	--	--	---	---	---

Power Location	Power Type	Voltage	Emergency Power	LED Type
Integral Power IP Integral Power Small Round Canopy 2R25 25' (76.2m) Wire Harness 2R50 50' (15.24m) Wire Harness 2R75 75' (22.9m) Wire Harness 2R100 100' (30.5m) Wire Harness	Flexible 1 to 1 Power AE eldoLED 0-10v, 1.0% Dimming AT eldoLED 0-10v, 0.1% Dimming AD eldoLED DALI, 0.1% Dimming AX eldoLED DMX, 100-0.1% Dimming AH Hi-lume 1% EcoSystem, Soft On / Fade to Black Technology, LDE1 AH2 Hi-lume 1% 2-wire LTEA2W (120V forward phase only) Optimized Power AEO eldoLED 0-10v, 1.0% Dimming ATO eldoLED 0-10v, 0.1% Dimming ADO eldoLED DALI, 0.1% Dimming AXO eldoLED DMX, 100-0% Dimming ZZ Other (please specify)	1 120v 2 120v-277v X Not Yet Specified	0 No Emergency Power ZZ Emergency Power (specify requirements)	Z Zipper Board™
*See Power Guide for driver features & limitations.				

»			0
---	--	--	---

Lumen Output	Color Temperature	Optics	Sensors
LO Low Output SO Standard Output HO High Output* ZZ Other (please specify) See IES Files page for details. *See Power Guide for driver features & limitations.	80+ CRI 27 2700K 30 3000K 35 3500K 40 4000K 90+ CRI 279 2700K 309 3000K 359 3500K 409 4000K ZZ Tunable White Available See Guide for details	A3 Square 3535/30, Soft Wash	0 None ZZ Other (please specify)*

»	
---	--

Finish	Options
WH White	0 None
BL Black	9 9' 18/3 Cord and Plug

NOTES & LIMITATIONS

*Sensors available. Contact [Vode](#) for more information.
Contact factory for Chicago Plenum

5 Year Limited Warranty. See full Vode warranty description [here](#) or at [vode.com](#).

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA.



Applications

General Interior and Open Office



Square 3535/30, Soft Wash

Structure


Rail Lengths	24" (610mm) - 144" (3658mm) See Rail Length Chart for more details
Rail Dimensions	1.38" (35mm) x 2.11" (54mm) / 30°. See <i>dimensions section, page 7</i> , for details
Construction	Extruded and machined 6063 aluminum
Mounting	Ceiling mount to jbox or driver housing
Cable Length	48" (1220mm) and 96" (2438mm) available. Field adjustable. Non-standard cable lengths available.
System Run Length	24" (610mm) minimum. Unlimited maximum length
Operating Temperature	32°F to 104°F (0°C to 40°C)
Humidity	0-85%, non-condensing
System Weight	0.39 lbs per foot (0.18 kg per 305mm) power supply and housing not included

Materials


LED Board Construction	Aluminum core PCB, black LCP connectors, RoHS compliant
Lens	High-impact extruded acrylic glass (PMMA).
Suspension Cable	Ø4mm, 22/4 AWG, TPE jacket, FEP-insulated, Red List Approved
Power Cable	Ø3mm, 33/2 AWG, Plenum (CMP) rated semi-rigid PVC or FEP, flame tested UL-910, Red List Approved
Cable Connectors	Unfilled black nylon, rated UL 94 V-0, halogen free, PVC or FEP overmold, RoHS compliant, Red List Approved.
Remote Linear Power Housing	20.7" x 2.375" x 2.53", 0.054" formed Galvanized Steel.
Remote Brick Power Housing	4.32" x 3.37" x .078" Galvanized Steel mounting plate
Integral Power Housing	extruded and machined 6063 aluminum
Center Cable Suspension	3/64" aircraft cable

Mounting Options

Remote Power




Small Round
Canopy
Ø2.5" (51mm)




Center Support Cable
108" - 144" Rails Only
*Center Support Cable for
mounting to T-Bar tile available.*

Integral Power (24"-72")




Integral Power
(end)
h 1.8" (46mm)
w 1.7" (43mm)




Integral Power
(joint)

24" - 96" Rail Dimensions




Layout




Corner and Shapes Available. See [Corners and Shapes Guide](#).

108" - 144" Rail Dimensions



Layout




Corner and Shapes Available. See [Corners and Shapes Guide](#).

Power and Controls

Power Type	Class 2 (<60v output) constant current driver
Dimming Controls	Dimming (0.1%, 1%), 0-10v, DALI, DMX, Lutron Hi-lume 1% are available. See Power Guide for details.
Input Voltage	120v - 277v, 50/60hz
Power Location	Remote power. Maximum remote distance up to 100' (30.5m) <i>depending</i> on driver selection. See Power Guide for details.


Remote power is locating the power supply away from the fixture. Remote power comes in two housing styles: brick style and linear style. Consult [Power Guide](#) to determine which type you will receive.

Remote Brick Power Housing




Supplied for some remote power applications. One remote power supply housing is supplied for each rail. Provided driver mounting plate fits standard 4" metal, square J-Boxes with a minimum volume of 21 in³ (J-Box not provided). See [Tech Sheet](#) for details.

Remote Linear Power Housing




One remote power supply housing is supplied with each power supply. All Vode linear remote drivers come in a 0.054" (0.8mm) formed galvanized steel power supply housing with five (5) knockouts: (4) 1-1/8", (1) 7/8" and (1) 9/16". Accommodates standard linear power supplies. See [Tech Sheet](#) for details.

Integral Power



Houses integral power supply. Direct conduit feed is recommended, but integral power supply housing will mount to any standard North America 4" j-box. Mounts to most surfaces. Blocking is recommended at all arm junctions. See [Tech Sheet](#) for details.

Wire Harness




Wire harness connects driver to rail. Wire harness is 25' (7.6m) with micro fit molex connectors for quick and easy installation. Wire harnesses are also available in 50' (15m), 75' (22.9m), and 100' (30.5m). See [Tech Sheet](#) for details.

Power and Controls

Flexible 1 to 1 power

For Flexible 1 to 1 Power, Vode supplies one single output driver per fixture, allowing each fixture to be controlled independently. Direct/Indirect fixtures are supplied with two single output drivers, allowing the direct and indirect lighting to be controlled independently. Consult [Power Guide](#) to determine which type you will receive.




Note: Drawings not to scale, for reference only.

Optimized Power

To optimize power, Vode configures specifications with drivers that have 2 or 4 outputs. Depending on system configurations and power requirements, up to 4 fixtures can be powered from a 4-output driver. Consult [Power Guide](#) to determine which type you will receive.

IMPORTANT: Each fixture will still require individual wire harnesses, as shown below.



Finish

White Painted Finish



White Rail, White Canopy/Integral Power, White Cable

Black Anodized Finish




Black Rail, Black Canopy/Integral Power, Black Cable

Note: Drawings not to scale, for reference only.

Performance | Zipper LED

Zipper Board has 72 diodes per foot (305mm). Testing based on a 4' rail section. Lumen measurement complies with IES-LM-79-08 testing procedures.

Square 3535/30, Soft Wash, white finish (A3-WH)



L80 >60,000 hours

80 CRI (80min., 84 avg.)

Low Output (LO)

	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	94	96	96	79	81	83	84
Lumens per foot (305mm)	338	349	356	356	292	301	307	310
Watts per foot (305mm)	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8

90 CRI (90min., 96 avg.)


Standard Output (SO)

	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	104	107	110	110	90	93	95	96
Lumens per foot (305mm)	677	698	712	712	583	602	614	620
Watts per foot (305mm)	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6

High Output (HO)

	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	103	106	109	109	89	92	94	95
Lumens per foot (305mm)	1015	1047	1068	1068	875	903	921	930
Watts per foot (305mm)	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9

Square 3535/30, Soft Wash, black finish (A3-BL)



L80 >60,000 hours

80 CRI (80min., 84 avg.)

Low Output (LO)

	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	69	71	72	72	59	61	63	63
Lumens per foot (305mm)	255	263	268	268	219	226	231	233
Watts per foot (305mm)	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8

90 CRI (90min., 96 avg.)

Standard Output (SO)

	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	78	81	83	83	68	70	71	72
Lumens per foot (305mm)	509	525	536	536	439	453	462	467
Watts per foot (305mm)	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6

High Output (HO)

	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	78	80	82	82	67	69	71	71
Lumens per foot (305mm)	764	788	804	804	658	679	693	700
Watts per foot (305mm)	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9

© 2021 Vode Lighting LLC. All rights reserved.

The Vode logo and Vode, ZipTwo, MicroBaffle and Zipper Board names are either registered trademarks or trademarks of Vode Lighting LLC in the United States and/or other countries. All other brand or product names are trademarks or registered trademarks of their respective owners. Due to ongoing innovation, specifications may change without notice.