

## IES Report



# ZipTwo® | 707 | Round 3515, Diffuse | 80 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-35-S4-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	109	112	114	114
Total Lumens, 4' rail length (1219mm)	1612	1663	1697	1697
Lumens per foot (305mm)	403	416	424	424
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# ZipTwo® | 707 | Round 3515, Diffuse | 80 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-35-S4-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	124	128	130	130
Total Lumens, 4' rail length (1219mm)	3224	3326	3393	3393
Lumens per foot (305mm)	806	831	848	848
Input Power (W), 4' rail length (1219mm)	26.1	26.1	26.1	26.1
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# ZipTwo® | 707 | Round 3515, Diffuse | 80 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-35-S4-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	123	127	129	129
Total Lumens, 4' rail length (1219mm)	4836	4988	5090	5090
Lumens per foot (305mm)	1209	1247	1273	1273
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# ZipTwo® | 707 | Round 3515, Diffuse | 90 CRI | LO

707-Z2-4-48-XX-XX-X-0-Z-LO-359-S4-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	94	97	99	100
Total Lumens, 4' rail length (1219mm)	1390	1433	1463	1477
Lumens per foot (305mm)	347	358	366	369
Input Power (W), 4' rail length (1219mm)	14.9	14.9	14.9	14.9
Watts per foot (305mm)	3.8	3.8	3.8	3.8
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report



# ZipTwo® | 707 | Round 3515, Diffuse | 90 CRI | SO

707-Z2-4-48-XX-XX-X-0-Z-SO-359-S4-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	106	110	113	113
Total Lumens, 4' rail length (1219mm)	2779	2867	2925	2955
Lumens per foot (305mm)	695	717	731	739
Input Power (W), 4' rail length (1219mm)	26.2	26.2	26.1	26.2
Watts per foot (305mm)	6.6	6.6	6.6	6.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES Report

# ZipTwo® | 707 | Round 3515, Diffuse | 90 CRI | HO

707-Z2-4-48-XX-XX-X-0-Z-HO-359-S4-X-WH-0

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	106	109	111	113
Total Lumens, 4' rail length (1219mm)	4169	4300	4388	4432
Lumens per foot (305mm)	1042	1075	1097	1108
Input Power (W), 4' rail length (1219mm)	39.6	39.6	39.6	39.6
Watts per foot (305mm)	9.9	9.9	9.9	9.9
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).