

## IES Report

# BoxRail® | 207 | White Baffle, down | 90 CRI | LO

207-BX-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-WB-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	59	61	62	63
Total Lumens, 4' rail length (1219mm)	847	874	891	900
Lumens per foot (305mm)	212	218	223	225
Input Power (W), 4' rail length (1219mm)	14.4	14.4	14.4	14.4
Watts per foot (305mm)	3.6	3.6	3.6	3.6
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : VODE\_207\_BX\_LO\_359\_WB.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] L022010909 (SOURCE REPORT FOR REFERENCE)

[TESTLAB] REPORT BASED ON DATA FROM NVLAP ACCREDITED LAB

[ISSUE DATE] 12/23/2019

[MANUFAC] Vode Lighting

[LUMCAT] 207-BX-48-Z-LO-359-WB

[LUMINAIRE] BoxRail LED, 48", 3500K, 90 CRI, zipper board,

[MORE] white baffle w/clear lens down, low output

[TEST PROCEDURE] IESNA:LM-79-08

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	891
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	62
Total Luminaire Watts	14.38
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.28
Spacing Criterion (90-270)	0.78
Spacing Criterion (Diagonal)	0.98
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.08 ft
Luminous Width (90-270)	4.00 ft
Luminous Height	0.09 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1968	4132	5903
55	1540	2375	4797
65	1118	1335	3793
75	337	516	2515
85	139	150	920

IES INDOOR REPORT  
PHOTOMETRIC FILENAME : VODE\_207\_BX\_LO\_359\_WB.IES

CANDELA TABULATION

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
<b>0</b>	678.5	678.5	678.5	678.5	678.5	678.5	678.5	678.5	678.5	678.5
<b>5</b>	674.0	671.5	669.0	666.5	664.5	662.0	660.0	658.0	656.5	655.0
<b>10</b>	666.0	661.0	656.0	651.5	647.0	643.0	639.0	630.5	622.5	615.5
<b>15</b>	653.5	646.5	639.5	633.0	625.5	611.5	598.5	586.5	575.0	564.5
<b>20</b>	633.5	624.0	615.5	605.0	587.0	570.0	553.5	537.5	523.5	509.0
<b>25</b>	608.0	597.0	586.5	566.0	544.5	523.5	502.5	483.5	462.5	443.0
<b>30</b>	579.5	566.5	550.5	524.0	498.5	473.5	447.5	421.0	396.0	371.0
<b>35</b>	537.0	522.0	499.5	471.0	442.5	415.0	387.0	354.5	325.0	296.0
<b>40</b>	318.0	309.5	300.0	298.5	307.5	323.0	307.0	276.0	248.5	219.5
<b>45</b>	88.0	99.0	120.0	138.0	142.5	143.5	175.0	172.5	168.0	157.5
<b>50</b>	76.0	78.0	82.0	86.5	92.0	101.0	108.0	115.0	117.5	116.5
<b>55</b>	68.5	69.5	71.5	74.5	77.0	81.0	84.5	85.5	86.5	87.5
<b>60</b>	61.5	61.5	61.0	60.0	60.0	61.5	62.0	63.0	64.0	65.0
<b>65</b>	48.0	47.0	44.0	43.0	42.5	42.5	43.0	43.5	44.5	46.0
<b>70</b>	28.0	27.0	26.0	26.0	26.5	26.5	26.5	27.0	28.0	29.5
<b>75</b>	13.5	13.0	14.5	14.0	14.0	14.0	14.0	14.0	15.0	16.0
<b>80</b>	8.5	9.0	8.5	8.5	8.0	8.0	7.5	7.5	7.5	7.5
<b>85</b>	5.0	5.5	5.5	5.5	5.5	5.0	5.0	4.5	4.5	4.0
<b>90</b>	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0

Vert. Angles      Horizontal Angles

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>
<b>0</b>	678.5	678.5	678.5	678.5	678.5	678.5	678.5	678.5	678.5
<b>5</b>	653.5	652.0	651.0	650.5	649.5	649.5	649.0	649.0	649.5
<b>10</b>	609.0	603.5	598.5	594.0	590.5	587.5	585.5	584.5	585.0
<b>15</b>	554.0	545.0	536.5	530.0	525.0	520.5	518.0	516.5	517.0
<b>20</b>	494.5	480.0	468.0	457.0	448.5	442.0	437.5	434.5	435.0
<b>25</b>	425.5	408.0	391.5	378.0	366.5	358.0	352.0	347.0	347.0
<b>30</b>	348.5	328.5	310.0	293.5	280.0	268.5	260.0	255.0	254.5
<b>35</b>	269.0	245.5	228.0	214.0	203.0	195.5	190.0	186.0	184.5
<b>40</b>	198.5	177.5	167.0	162.5	159.5	157.5	155.5	153.5	153.0
<b>45</b>	150.0	144.5	140.0	136.0	133.0	131.0	129.0	127.5	127.0
<b>50</b>	117.0	115.0	112.5	110.5	108.5	106.5	105.5	104.5	104.0
<b>55</b>	88.5	88.0	88.5	88.0	87.0	86.0	85.0	84.5	84.5
<b>60</b>	66.0	66.5	67.0	67.5	67.5	67.0	66.5	66.0	66.0
<b>65</b>	47.0	48.0	49.0	49.5	49.5	50.0	49.5	49.5	50.0
<b>70</b>	30.5	32.5	34.0	33.5	34.0	35.0	35.0	36.0	38.0
<b>75</b>	17.0	18.0	19.5	20.0	20.0	21.0	21.0	21.0	21.0
<b>80</b>	7.5	8.0	8.5	9.0	9.5	9.5	10.0	10.0	10.0
<b>85</b>	4.0	4.0	3.5	3.5	3.0	3.0	3.0	3.0	3.0
<b>90</b>	1.5	1.5	1.5	1.0	1.0	1.0	1.0	1.0	0.5

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : VODE\_207\_BX\_LO\_359\_WB.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	222.22	N.A.	24.90
0-30	431.41	N.A.	48.40
0-40	628.57	N.A.	70.50
0-60	820.88	N.A.	92.10
0-80	886.38	N.A.	99.40
0-90	891.43	N.A.	100.00
10-90	829.81	N.A.	93.10
20-40	406.35	N.A.	45.60
20-50	524.15	N.A.	58.80
40-70	238.69	N.A.	26.80
60-80	65.50	N.A.	7.30
70-80	19.13	N.A.	2.10
80-90	5.05	N.A.	0.60
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	891.43	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	61.62
10-20	160.60
20-30	209.19
30-40	197.16
40-50	117.80
50-60	74.51
60-70	46.38
70-80	19.13
80-90	5.05
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : VODE\_207\_BX\_LO\_359\_WB.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	91	90
2	104	98	93	88	102	96	91	87	93	89	85	90	86	83	87	84	82	80
3	97	89	82	77	95	87	81	77	85	80	75	82	78	74	80	76	73	71
4	91	81	74	69	89	80	73	68	78	72	67	75	71	67	73	69	66	64
5	85	74	67	62	83	73	66	61	71	65	61	70	64	60	68	63	60	58
6	79	68	61	56	78	68	61	56	66	60	55	64	59	55	63	58	54	53
7	75	63	56	51	73	63	56	51	61	55	50	60	54	50	59	54	50	48
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	42	41
10	63	51	44	40	62	51	44	40	50	44	40	49	43	40	48	43	39	38

POLAR GRAPH



Maximum Candela = 678.5 Located At Horizontal Angle = 0, Vertical Angle = 0  
# 1 - Vertical Plane Through Horizontal Angles (0 - 180)  
# 2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)