

## IES Report

# BoxRail® | 207 | Wide Batwing, up | 80 CRI | HO

207-BX-XX-4-48-XX-XX-XX-X-X-Z-HO-35-G1-X-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	110	113	116	116
Total Lumens, 4' rail length (1219mm)	5645	5823	5942	5942
Lumens per foot (305mm)	1411	1456	1485	1485
Input Power (W), 4' rail length (1219mm)	51.6	51.6	51.6	51.6
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : VODE\_207\_BX\_HO\_35\_G1.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] L022010902 (SOURCE REPORT FOR REFERENCE)

[TESTLAB] REPORT BASED ON DATA FROM NVLAP ACCREDITED LAB

[ISSUE DATE] 12/23/2019

[MANUFAC] Vode Lighting

[LUMCAT] 207-BX-48-Z-HO-35-G1

[LUMINAIRE] BoxRail LED, 48", 3500K, 80 CRI, zipper board, wide batwing lens up,

[MORE] high output, clear anodized finish

[TEST PROCEDURE] IESNA:LM-79-08

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	5931
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	115
Total Luminaire Watts	51.57
Ballast Factor	1.00
CIE Type	Indirect
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.08 ft
Luminous Width (90-270)	4.00 ft
Luminous Height	0.09 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	0	0	0
55	0	0	0
65	0	0	0
75	0	0	0
85	0	0	0

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : VODE\_207\_BX\_HO\_35\_G1.IES**

**CANDELA TABULATION**

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
<b>90</b>	10.736	10.736	10.736	10.736	10.736	10.736	10.736	10.736	10.736	10.736
<b>95</b>	49.984	61.490	58.014	59.334	61.336	64.702	66.374	79.706	87.318	93.192
<b>100</b>	193.072	202.642	207.416	217.294	230.010	243.562	259.182	272.382	290.026	291.566
<b>105</b>	463.430	431.662	461.956	474.056	487.872	510.444	527.560	541.992	555.654	552.156
<b>110</b>	863.984	835.560	838.420	856.680	886.204	887.788	918.522	895.884	873.224	818.994
<b>115</b>	1381.996	1376.320	1327.568	1302.466	1290.674	1283.502	1248.302	1198.912	1136.234	1058.640
<b>120</b>	1758.746	1747.746	1723.524	1677.962	1636.118	1577.576	1515.426	1444.894	1336.324	1222.650
<b>125</b>	2003.826	1991.022	1961.300	1923.746	1876.798	1788.226	1708.300	1592.492	1476.420	1345.718
<b>130</b>	2108.590	2097.282	2064.876	2015.838	1956.108	1876.600	1775.598	1666.016	1540.682	1411.828
<b>135</b>	2107.468	2097.942	2067.648	2019.974	1954.040	1877.634	1781.054	1680.932	1565.190	1449.602
<b>140</b>	2039.246	2029.522	2002.044	1959.320	1902.538	1831.962	1748.582	1657.810	1560.746	1460.998
<b>145</b>	1931.534	1922.866	1900.910	1866.964	1818.850	1760.286	1691.998	1614.448	1533.994	1451.912
<b>150</b>	1806.134	1798.302	1782.242	1754.566	1717.650	1671.010	1616.186	1556.720	1496.000	1429.978
<b>155</b>	1675.938	1670.240	1659.614	1638.450	1611.742	1577.576	1537.382	1494.218	1449.382	1404.018
<b>160</b>	1553.486	1550.472	1541.760	1529.814	1510.806	1489.136	1464.232	1434.290	1402.874	1374.736
<b>165</b>	1448.568	1446.346	1440.846	1434.356	1425.556	1412.422	1397.836	1381.886	1364.704	1344.816
<b>170</b>	1370.182	1368.972	1366.310	1363.340	1359.666	1355.354	1350.404	1342.572	1334.454	1325.984
<b>175</b>	1323.168	1322.596	1322.134	1320.748	1319.714	1318.592	1317.382	1316.084	1314.720	1313.290
<b>180</b>	1306.800	1306.800	1306.800	1306.800	1306.800	1306.800	1306.800	1306.800	1306.800	1306.800

**Vert. Angles**      **Horizontal Angles**

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>
<b>90</b>	10.736	10.736	10.736	10.736	10.736	10.736	10.736	10.736	10.736
<b>95</b>	94.578	117.018	114.290	91.718	85.316	85.888	84.194	81.070	82.808
<b>100</b>	291.104	289.894	268.488	239.162	219.186	201.498	185.658	179.608	180.356
<b>105</b>	536.998	495.242	446.864	389.818	347.116	315.414	292.666	281.138	279.378
<b>110</b>	743.710	676.148	602.316	526.526	469.546	431.244	403.568	389.576	388.938
<b>115</b>	956.274	843.106	741.532	654.302	587.928	542.498	511.192	494.494	493.130
<b>120</b>	1100.968	972.004	860.288	770.726	698.786	649.682	619.696	600.358	592.526
<b>125</b>	1207.008	1078.990	965.602	871.772	796.620	745.052	714.054	695.310	686.026
<b>130</b>	1283.612	1163.822	1056.660	964.370	889.724	833.690	795.938	772.002	754.072
<b>135</b>	1333.046	1225.070	1125.674	1043.108	974.534	922.482	888.096	866.712	857.890
<b>140</b>	1360.480	1268.784	1182.764	1106.380	1046.650	997.568	964.788	944.812	935.528
<b>145</b>	1371.282	1295.096	1224.014	1160.192	1107.986	1066.934	1036.156	1020.052	1010.768
<b>150</b>	1367.982	1308.318	1250.524	1202.938	1158.190	1128.160	1100.616	1089.264	1081.586
<b>155</b>	1357.576	1313.136	1272.458	1232.836	1204.302	1179.068	1160.236	1150.446	1143.362
<b>160</b>	1345.014	1313.598	1283.238	1261.524	1240.580	1220.428	1211.606	1204.126	1198.494
<b>165</b>	1326.358	1311.222	1296.064	1281.016	1266.166	1259.412	1253.780	1248.654	1244.606
<b>170</b>	1317.250	1308.340	1299.518	1295.294	1291.422	1287.814	1284.492	1281.368	1278.728
<b>175</b>	1311.816	1310.298	1308.736	1307.174	1305.612	1304.050	1302.466	1300.992	1299.562
<b>180</b>	1306.800	1306.800	1306.800	1306.800	1306.800	1306.800	1306.800	1306.800	1306.800

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : VODE\_207\_BX\_HO\_35\_G1.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	0.00	N.A.	0.00
0-30	0.00	N.A.	0.00
0-40	0.00	N.A.	0.00
0-60	0.00	N.A.	0.00
0-80	0.00	N.A.	0.00
0-90	0.00	N.A.	0.00
10-90	0.00	N.A.	0.00
20-40	0.00	N.A.	0.00
20-50	0.00	N.A.	0.00
40-70	0.00	N.A.	0.00
60-80	0.00	N.A.	0.00
70-80	0.00	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	594.85	N.A.	10.00
90-120	1543.6	N.A.	26.00
90-130	2726.89	N.A.	46.00
90-150	4770.53	N.A.	80.40
90-180	5930.74	N.A.	100.00
110-180	5335.89	N.A.	90.00
0-180	5930.74	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	0.00
10-20	0.00
20-30	0.00
30-40	0.00
40-50	0.00
50-60	0.00
60-70	0.00
70-80	0.00
80-90	0.00
90-100	111.48
100-110	483.37
110-120	948.74
120-130	1183.29
130-140	1127.03
140-150	916.61
150-160	651.71
160-170	382.81
170-180	125.69


**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : VODE\_207\_BX\_HO\_35\_G1.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	95	95	95	95	81	81	81	81	56	56	56	32	32	32	10	10	10	0
1	87	83	79	76	74	71	68	65	48	47	45	28	27	26	9	9	8	0
2	79	72	66	62	67	62	57	53	42	40	37	24	23	22	8	7	7	0
3	72	63	56	51	61	54	49	44	37	34	31	21	20	18	7	6	6	0
4	65	56	48	43	56	48	42	37	33	29	26	19	17	16	6	6	5	0
5	60	49	42	36	51	42	36	32	29	25	22	17	15	13	5	5	4	0
6	55	44	36	31	47	38	32	27	26	22	19	15	13	11	5	4	4	0
7	50	39	32	27	43	34	28	23	23	19	17	14	11	10	4	4	3	0
8	47	35	28	23	40	30	24	20	21	17	14	12	10	9	4	3	3	0
9	43	32	25	20	37	28	22	18	19	15	13	11	9	8	4	3	3	0
10	40	29	22	18	34	25	19	16	17	14	11	10	8	7	3	3	2	0

POLAR GRAPH



Maximum Candela = 2108.59 Located At Horizontal Angle = 0, Vertical Angle = 130  
# 1 - Vertical Plane Through Horizontal Angles (0 - 180)  
# 2 - Horizontal Cone Through Vertical Angle (130) (Through Max. Cd.)